

Product information

26 15 200 T

Snipe Nose Side Cutting Pliers

(Stork Beak Pliers)

DIN ISO 5745





You

General


EAN4003773079996Plierschrome-platedHeadchrome-platedHandleswith multi-component grips, with integrated tether attachment point for a tool tetherWeight204 gDimensions200 x 57 x 20 mmStandardDIN ISO 5745REACH compliantdoes not contain SVHCRoHS compliantnot applicableCutting capacities medium hard wire (diameter)Ø 3.2 mmSchneidwerte harter Draht (Durchmesser)Ø 2.2 mmJaw thickness (joint) (T1)9.5 mmTips width (W4)3.0 mmTips thickness (T2)2.5 mmJaw length (L3)18 mm	Contorui	
Plierschrome-platedHeadchrome-platedHandleswith multi-component grips, with integrated tether attachment point for a tool tetherWeight204 gDimensions200 x 57 x 20 mmStandardDIN ISO 5745REACH compliantdoes not contain SVHCRoHS compliantnot applicableCutting capacities medium hard wire (diameter)Ø 3.2 mmSchneidwerte harter Draht (Durchmesser)Ø 2.2 mmJaw thickness (joint) (T1)9.5 mmTips width (W4)3.0 mmTips thickness (T2)2.5 mmJaw length (L3)73.0 mmHead width (W3)18 mm	Article No.	26 15 200 T
Headchrome-platedHeadwith multi-component grips, with integrated tether attachment point for a tool tetherWeight204 gDimensions200 x 57 x 20 mmStandardDIN ISO 5745REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities medium hard wire (diameter)Ø 3.2 mm9.5 mmJaw thickness (joint) (T1)9.5 mmTips width (W4)3.0 mmTips thickness (T2)2.5 mmJaw length (L3)73.0 mmHead width (W3)18 mm	EAN	4003773079996
Handleswith multi-component grips, with integrated tether attachment point for a tool tetherWeight204 gDimensions200 x 57 x 20 mmStandardDIN ISO 5745REACH compliantdoes not contain SVHCRoHS compliantnot applicableCutting capacities medium hard wire (diameter)Ø 3.2 mmØ 3.2 mmSchneidwerte harter Draht (Durchmesser)Ø 2.2 mmJaw thickness (joint) (T1)9.5 mmTips width (W4)3.0 mmTips thickness (T2)2.5 mmJaw length (L3)73.0 mmHead width (W3)18 mm	Pliers	chrome-plated
for a tool tetherWeight204 gDimensions200 x 57 x 20 mmStandardDIN ISO 5745REACH compliantdoes not contain SVHCRoHS compliantnot applicableCutting capacities medium hard wire (diameter)Q 3.2 mmQ 3.2 mmSchneidwerte harter Draht (Durchmesser)Q 2.2 mmJaw thickness (joint) (T1)9.5 mmTips width (W4)3.0 mmTips thickness (T2)2.5 mmJaw length (L3)73.0 mmHead width (W3)18 mm	Head	chrome-plated
Dimensions200 x 57 x 20 mmStandardDIN ISO 5745REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities medium hard wire (diameter)Ø 3.2 mmSchneidwerte harter Draht (Durchmesser)Ø 2.2 mmJaw thickness (joint) (T1)9.5 mmTips width (W4)3.0 mmTips thickness (T2)2.5 mmJaw length (L3)73.0 mmHead width (W3)18 mm	Handles	
StandardDIN ISO 5745REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities medium hard wire (diameter)Ø 3.2 mmSchneidwerte harter Draht (Durchmesser)Ø 2.2 mmJaw thickness (joint) (T1)9.5 mmTips width (W4)3.0 mmTips thickness (T2)2.5 mmJaw length (L3)73.0 mmHead width (W3)18 mm	Weight	204 g
REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities medium hard wire (diameter)Ø 3.2 mmSchneidwerte harter Draht (Durchmesser)Ø 2.2 mmJaw thickness (joint) (T1)9.5 mmTips width (W4)3.0 mmTips thickness (T2)2.5 mmJaw length (L3)73.0 mmHead width (W3)18 mm	Dimensions	200 x 57 x 20 mm
RoHS compliantnot applicableTechnical detailsCutting capacities medium hard wire (diameter)Ø 3.2 mmSchneidwerte harter Draht (Durchmesser)Ø 2.2 mmJaw thickness (joint) (T1)9.5 mmTips width (W4)3.0 mmTips thickness (T2)2.5 mmJaw length (L3)73.0 mmHead width (W3)18 mm	Standard	DIN ISO 5745
Technical detailsCutting capacities medium hard wire (diameter)Ø 3.2 mmSchneidwerte harter Draht (Durchmesser)Ø 2.2 mmJaw thickness (joint) (T1)9.5 mmTips width (W4)3.0 mmTips thickness (T2)2.5 mmJaw length (L3)73.0 mmHead width (W3)18 mm	REACH compliant	does not contain SVHC
Cutting capacities medium hard wire (diameter)Ø 3.2 mmSchneidwerte harter Draht (Durchmesser)Ø 2.2 mmJaw thickness (joint) (T1)9.5 mmTips width (W4)3.0 mmTips thickness (T2)2.5 mmJaw length (L3)73.0 mmHead width (W3)18 mm	RoHS compliant	not applicable
(diameter)Ø 2.2 mmSchneidwerte harter Draht (Durchmesser)Ø 2.2 mmJaw thickness (joint) (T1)9.5 mmTips width (W4)3.0 mmTips thickness (T2)2.5 mmJaw length (L3)73.0 mmHead width (W3)18 mm	Technical details	
Jaw thickness (joint) (T1)9.5 mmTips width (W4)3.0 mmTips thickness (T2)2.5 mmJaw length (L3)73.0 mmHead width (W3)18 mm	Cutting capacities medium hard wire (diameter)	Ø 3.2 mm
Tips width (W4)3.0 mmTips thickness (T2)2.5 mmJaw length (L3)73.0 mmHead width (W3)18 mm	Schneidwerte harter Draht (Durchmesser)	Ø 2.2 mm
Tips thickness (T2)2.5 mmJaw length (L3)73.0 mmHead width (W3)18 mm	Jaw thickness (joint) (T1)	9.5 mm
Jaw length (L3)73.0 mmHead width (W3)18 mm	Tips width (W4)	3.0 mm
Head width (W3) 18 mm	Tips thickness (T2)	2.5 mm
	Jaw length (L3)	73.0 mm
Drop Protection System yes	Head width (W3)	18 mm
	Drop Protection System	yes

- Half-round, long, tapered jaws
- Distortion-tolerant, elastic precision tips
- Suitable for finer gripping and cutting work, also on easy and semidifficult to reach areas
- Pliers with tether attachment point for mounting a fall protection system
- With cutting edges for soft, medium-hard and hard wire
- Cutting edges additionally induction-hardened, cutting edge hardness approx. 61 HRC

KNIPEX Quality – Made in Germany



Technical details



technical change and errors excepted



