

Product information

70 01 160 EAN

Diagonal Cutter

DIN ISO 5749



- Narrow head style for use in confined areas
- ٠
- The indispensable diagonal cutter for all-round use High-quality material and precise workmanship for long service life •
- Precision cutting edges for soft and hard wire
- Clean cutting of thin copper wires, also at the cutting edge tips ٠
- Cutting edges additionally induction-hardened, cutting edge hardness • approx. 62 HRC

General

Article No.70 01 160 EANEAN4003773022947Pliersblack atramentizedHeadpolishedHandlesplastic coatedWeight171 gDimensions160 x 50 x 14 mmStandardDIN ISO 5749REACH compliantdoes not contain SVHCRoHS compliantØ 4.0 mmCutting capacities soft wire (diameter)Ø 4.0 mmCutting capacities hard wire (diameter)Ø 3.0 mmCutting capacities hard wire (diameter)Ø 2.0 mm		
Pliersblack atramentizedHeadpolishedHandlesplastic coatedWeight171 gDimensions160 x 50 x 14 mmStandardDIN ISO 5749REACH compliantdoes not contain SVHCRoHS compliantnot applicableCutting capacities soft wire (diameter)Ø 4.0 mmØ 3.0 mm	Article No.	70 01 160 EAN
HeadpolishedHandlesplastic coatedWeight171 gDimensions160 x 50 x 14 mmStandardDIN ISO 5749REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities soft wire (diameter)Ø 4.0 mmCutting capacities medium hard wire (diameter)Ø 3.0 mm	EAN	4003773022947
Handlesplastic coatedWeight171 gDimensions160 x 50 x 14 mmStandardDIN ISO 5749REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities soft wire (diameter)Ø 4.0 mmCutting capacities medium hard wire (diameter)Ø 3.0 mm	Pliers	black atramentized
Weight171 gDimensions160 x 50 x 14 mmStandardDIN ISO 5749REACH compliantdoes not contain SVHCRoHS compliantnot applicableCutting capacities soft wire (diameter)Ø 4.0 mmØ 3.0 mm	Head	polished
Dimensions160 x 50 x 14 mmStandardDIN ISO 5749REACH compliantdoes not contain SVHCRoHS compliantnot applicableCutting capacities soft wire (diameter)Ø 4.0 mmØ 3.0 mmCutting capacities medium hard wire (diameter)Ø 3.0 mm	Handles	plastic coated
StandardDIN ISO 5749REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities soft wire (diameter)Ø 4.0 mmCutting capacities medium hard wire (diameter)Ø 3.0 mm	Weight	171 g
REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities soft wire (diameter)Ø 4.0 mmCutting capacities medium hard wire (diameter)Ø 3.0 mm	Dimensions	160 x 50 x 14 mm
RoHS compliantnot applicableTechnical detailsCutting capacities soft wire (diameter)Ø 4.0 mmCutting capacities medium hard wire (diameter)Ø 3.0 mm	Standard	DIN ISO 5749
Technical details Cutting capacities soft wire (diameter) Ø 4.0 mm Cutting capacities medium hard wire (diameter) Ø 3.0 mm	REACH compliant	does not contain SVHC
Cutting capacities soft wire (diameter)Ø 4.0 mmCutting capacities medium hard wire (diameter)Ø 3.0 mm	RoHS compliant	not applicable
Cutting capacities medium hard wire Ø 3.0 mm (diameter)	Technical details	
(diameter)	Cutting capacities soft wire (diameter)	Ø 4.0 mm
Cutting capacities hard wire (diameter) Ø 2.0 mm		Ø 3.0 mm
	Cutting capacities hard wire (diameter)	Ø 2.0 mm

technical change and errors excepted













