

## **Product information**

## 71 02 200 T

## **KNIPEX CoBolt®**

**Compact Bolt Cutter** 





- Micro-structured cutting edge reduces slipping of the material from the jaws
- With gripping surface below the joint for gripping and pulling wires from Ø 1.0 mm
- With slim multi-component grips without collar for better handling and easier transport
- With large contact surface on the handles for better allotment of pressure and more comfort at work
- Pliers with tether attachment point for mounting a fall protection system
- With precision cutting edges for soft, hard and piano wire
- Cuts bolts, nails, rivets, etc. up to Ø 5.2 mm
- Efficient joint design ensures exceptional cutting performance with little effort
- Cutting edges additionally induction-hardened, cutting edge hardness approx. 64 HRC

| ш | 8 | ш  | н |  |
|---|---|----|---|--|
| ı | ī | ub | e |  |
| ш |   | -  | ~ |  |

| General         |  |
|-----------------|--|
| Article No.     | 71 02 200 T  |
| EAN             | 4003773080046  |
| Pliers          | black atramentized   |
| Handles         | with slim multi-component grips, with integrated tether attachment point for a tool tether |
| Weight          | 375 g  |
| Dimensions      | 200 x 51 x 23 mm   |
| REACH compliant | contains SVHC  |
| RoHS compliant  | not applicable   |

| Technical details                              |          |
|--|----------|
| Cutting capacities soft wire (diameter)        | Ø 6 mm   |
| Cutting capacities medium hard wire (diameter) | Ø 5.2 mm |
| Schneidwerte harter Draht (Durchmesser)        | Ø 4.0 mm |
| Cutting capacities piano wire (diameter)       | Ø 3.6 mm |
| Drop Protection System                         | yes      |

technical change and errors excepted



With gripping surface below the joint for gripping and pulling wires from  $\ensuremath{\textsc{0}}$  1.0 mm