

Product information

74 06 200 T

High Leverage Diagonal Cutter

DIN ISO 5749 IEC 60900 DIN EN 60900

- Pliers with integrated, insulated tether attachment point for a tool tether
- For very tough, continuous use
- High cutting performance with minimum effort due to optimum coordination of the cutting edge angle and transmission ratio
- Precision cutting edges additionally induction-hardened (cutting edge hardness approx. 64 HRC), for all sorts of wire including piano wire



⚡ 1000 V 



| General | |
|------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Article No. | 74 06 200 T |
| EAN | 4003773081494 |
| Pliers | chrome-plated |
| Head | chrome-plated |
| Handles | insulated with multi-component grips, VDE-tested with integrated insulated tether attachment point for a tool tether |
| Weight | 305 g |
| Dimensions | 200 x 58 x 27 mm |
| Standard | DIN ISO 5749 DIN EN 60900 IEC 60900 |
| REACH compliant | does not contain SVHC |
| RoHS compliant | not applicable |
| Technical details | |
| Cutting capacities medium hard wire (diameter) | Ø 4.2 mm |
| Schneidwerte harter Draht (Durchmesser) | Ø 3.0 mm |
| Cutting capacities piano wire (diameter) | Ø 2.5 mm |
| Drop Protection System | yes |
| VDE tested | yes |

technical change and errors excepted