

Product information

77 42 115 ESD

Electronics Diagonal Cutters ESD

DIN ISO 9654 DIN EN 61 340-5




- · Pointed head, without bevel
- Cutting edge hardness approx. 57 HRC
- For fine cutting work, e.g. in electronics and fine mechanics
- Electrically discharging handles dissipative
- Sturdy, zero-backlash box joint
- Low-friction double spring for gentle and even opening
- The mirror polish together with a fine film of oil offer effective rust protection - no circuit faults caused by peeling chrome from plated tools
- Cutting edges additionally induction-hardened, cutting edge hardness approx. 62 HRC
- Handles with two-colour multi-component grips black/grey

WW	(A)		1
----	-----	--	---

General		
Article No.	77 42 115 ESD	
EAN	4003773031901	
Head	mirror polished	
Handles	with multi-component grips	
Weight	70 g	
Dimensions	115 x 54 x 17 mm	
Standard	DIN ISO 9654 DIN EN 61 340-5	
REACH compliant	does not contain SVHC	
RoHS compliant	not applicable	

Technical details	
Cutting capacities medium hard wire (diameter)	Ø 0.8 mm
Cutting capacities soft wire (diameter)	Ø 0.3 – 1.3 mm
Jaw length (B)	14 mm
Jaw thickness (joint) (D)	7 mm
Head width (A)	11 mm
ESD	yes



technical change and errors excepted

KNIPEX Quality – Made in Germany



