

## **Product information**

## 77 52 115

## **Electronics Diagonal Cutter**

**DIN ISO 9654** 




- Pointed, flat head, with small bevel
- Cutting edge hardness approx. 60 HRC
- For fine cutting work, e.g. in electronics and fine mechanics
- Load-optimised for a more direct feel when working
- Sturdy, zero-backlash box joint
- Low-friction double spring for gentle and even opening
- The polish or mirror polish together with a fine film of oil offer effective rust protection - no circuit faults caused by peeling chrome from plated tools
- Cutting edges additionally laser hardened, cutting edge hardness approx. 60 HRC
- Narrow sleeves pulled up to the head of the pliers enable the tool to be guided securely and comfortably, also between thumb and index finger



General	
Article No.	77 52 115
EAN	4003773040750
Head	mirror polished
Handles	with multi-component grips
Weight	65 g
Dimensions	115 x 66 x 17 mm
Standard	DIN ISO 9654
REACH compliant	does not contain SVHC
RoHS compliant	not applicable

Technical details	
Cutting capacities medium hard wire (diameter)	Ø 0.8 mm
Schneidwerte harter Draht (Durchmesser)	Ø 0.5 mm
Cutting capacities soft wire (diameter)	Ø 0.3 – 1 mm
Jaw length (B)	14 mm
Jaw thickness (joint) (D)	7.5 mm
Head width (A)	11 mm



technical change and errors excepted

## **KNIPEX** Quality – Made in Germany





