

Product information

95 62 160

Wire Rope Cutter

Also for high-strength wire rope



- Specially optimised for precise cutting of tyre cord, wire ropes up to Ø 2 mm and cables up to Ø 2 mm
- Ergonomic thanks to lightweight design and practical opening restriction
- Compact size, low weight, high performance level
- Made for intensive use: particularly durable and light at only 175 g
- For wire rope with Ø 4.00 / 1960 Nmm²
- Up to 30 % less physical effort compared to wire rope cutters of the same length
- Double-mounted box joint design for high level of stability
- Cutting edges additionally induction-hardened, cutting edge hardness approx. 62 HRC
- Convenient work thanks to opening spring
- Secured by locking device during transport

MM

General

Article No.	95 62 160
EAN	4003773082354
Shears	burnished
Head	burnished
Handles	with multi-component grips
Weight	175 g
Dimensions	160 x 61 x 21 mm
REACH compliant	does not contain SVHC
RoHS compliant	not applicable

Technical details

Cutting capacity copper cable, multiple-stranded (diameter)	Ø 6.0 mm
Cutting capacities wire rope (diameter)	Ø 4.0 mm

technical change and errors excepted



Compact at 160 mm but nevertheless more powerful than many larger wire rope cutters



Double-bearing joint



Cutting of high-strength wire ropes (1960 N/mm²) of up to Ø 4 mm