

Product information

97 33 01

KNIPEX MultiCrimp®

Lever Action Crimping Pliers with changer magazine


- The crimping dies 97 49 xx for the Crimp System Pliers 97 43 200 are not compatible with the KNIPEX MultiCrimp 97 33 01/02
- Just one tool for the most common crimping applications
- Crimping dies changed quickly and easily without any additional tool
- Sorted and protected storage of the interchangeable dies in a round magazine
- Comfortable, powerful crimping pliers in professional quality
- Same reliable crimping results as with fixed crimping dies
- Consistently high crimping quality thanks to precision dies and ratchet mechanism (unlockable)



General

| | |
|-----------------|----------------------------|
| Article No. | 97 33 01 |
| EAN | 4003773066927 |
| Pliers | burnished |
| Handles | with multi-component grips |
| Weight | 770 g |
| Dimensions | 250 x 75 x 28 mm |
| REACH compliant | contains SVHC |
| RoHS compliant | not applicable |

Technical details



| | |
|--------------------------------|---|
| Application | non-insulated, open flat plug connector (plug width 4.8 + 6.3 mm) |
| Capacity in square millimetres | 0.25 — 6.0 mm ² |
| Number of crimp profiles | 3 |
| AWG | 20 — 10 |

Accessories

| | |
|----------|--|
| 97 39 05 | Crimping die for non-insulated open plug type connectors (plug width 4.8 + 6.3 mm), |
| 97 39 09 | Crimping die for insulated and non-insulated wire ferrules, 10 / 16 / 25 mm ² |
| 97 39 06 | Crimping die for insulated cable lugs, plug connectors and butt connectors, |
| 97 39 08 | Crimping die for insulated and non-insulated wire ferrules, 0,25 - 6 mm ² |
| 97 39 13 | Crimping die for non-insulated crimp, |
| 97 39 90 | Changer magazine empty, |

technical change and errors excepted



Changing the crimping dies: unlock the magazine position, take out the set of dies which the pliers have been pushed on



Changing position: service lever opens out for parallel jaw positioning



Fold in the service lever and press the pliers – ready for use again

