

## **Product information**

## 97 52 35 SB

## **KNIPEX PreciForce®**

**Crimping Pliers** 

- Consistently high crimping quality thanks to precision dies and ratchet mechanism (unlockable)
- Tools have been set precisely (calibrated) in the factory
- Optimum transmission of force thanks to toggle lever for fatiguereduced operation
- Good handling thanks to favourable handle position, low weight, compact design and ergonomically shaped handles
- Crimping die is not exchangeable

## MM 🗖

\_

| General                        |                                                                   |
|--------------------------------|-------------------------------------------------------------------|
| Article No.                    | 97 52 35 SB                                                       |
| EAN                            | 4003773052562                                                     |
| Pliers                         | burnished                                                         |
| Handles                        | with multi-component grips                                        |
| Weight                         | 516 g                                                             |
| Dimensions                     | 220 x 115 x 26 mm                                                 |
| REACH compliant                | contains SVHC                                                     |
| RoHS compliant                 | not applicable                                                    |
| Technical details              |                                                                   |
| Application                    | non-insulated open plug type connectors - plug width 4.8 + 6.3 mm |
| Capacity in square millimetres | 0.5 — 6.0 mm <sup>2</sup>                                         |
| Number of crimp profiles       | 3                                                                 |
| AWG                            | 20 — 10                                                           |

technical change and errors excepted