

## Product information

# 97 52 65 A

## Four-Mandrel Crimping Pliers for turned contacts




- Basic pliers without locator for crimping turned pin and socket contacts from various contact manufacturers, for cable cross-sections from 0.14 to 6 mm<sup>2</sup>
- Fine adjustment of pressure depending on the conductor's diameter by means of adjusting wheel
- With table for calculating the settings
- Pliers in a plastic case with foam insert
- Crimp mandrel feed adjustable in steps of 0.01 mm using the adjusting wheel
- Reliable crimping thanks to synchronised feed of the crimping mandrels
- Process-secure and consistently high crimp quality thanks to IEC 60352-compliant trigger lock (positive lock, can be unlocked)
- Checking of default setting with enclosed test gauge
- Separately available contact holders enable the exact positioning of the crimp contacts
- Pliers in a plastic case with foam insert

### General

Part No.	97 52 65 A
EAN	4003773071594
Pliers	chrome-plated
Head	chrome-plated
Handles	with multi-component handles
Weight	604 g
Dimensions	230 x 79 x 42 mm
REACH compliant	contains SVHC
RoHS compliant	compliant

### Technical details



Application	turned contacts (Harting; Ilme; Phoenix; Amphenol®; Walther; HTS; Contact; Weidmüller)
Capacity in square millimetres	0.14 — 6 mm <sup>2</sup>
AWG	26 — 10
Number of crimp profiles	1
Max. contact diameter	7.5 mm

### Accessories

97 59 65 2	Universal Locator for 97 52 65 / 97 52 65 A / 97 52 65 DG / 97 52 65 DG A,
------------	--

technical change and errors excepted

