

Product information

97 52 65 DG A

Four-Mandrel Crimping Pliers for turned contacts




- Basic pliers without locator for crimping turned pin and socket contacts from various contact manufacturers, for cable cross-sections from 0.14 to 6 mm²
- Crimp mandrel feed adjustable in increments of 0.01 mm and digitally readable; setting in mm, inch or comparable selector settings according to MIL standard
- Electronic wear monitoring (patented) with warning function
- Process-secure and consistently high crimp quality thanks to IEC 60352-compliant trigger lock (positive lock, can be unlocked)
- With recalibration function; check basic setting using the enclosed test pin
- Separately available contact holders enable the exact positioning of the crimp contacts
- Pliers in a plastic case with foam insert

General

Part No.	97 52 65 DG A
EAN	4003773071990
Pliers	chrome-plated
Head	chrome-plated
Handles	with multi-component handles
Weight	633 g
Dimensions	240 x 86 x 19 mm
REACH compliant	contains SVHC
RoHS compliant	not applicable

Technical details

	
Application	turned contacts (Harting; Ilme; Phoenix; Amphenol®; Walther; HTS; Contact; Weidmüller)
Capacity in square millimetres	0.14 — 6 mm ²
AWG	26 — 10
Number of crimp profiles	1
Max. contact diameter	7.5 mm

Accessories

97 59 65 2	Universal Locator for 97 52 65 / 97 52 65 A / 97 52 65 DG / 97 52 65 DG A,
------------	--

technical change and errors excepted

