

Product information

97 52 65 DG A

Four-Mandrel Crimping Pliers for turned contacts



- Crimping capacity can be adjusted in increments of 0.01 mm •
- With digital display of the preset crimping capacities and possibility of • re-calibration via RESET function with electronic wear monitoring
- Adjustment in mm, inches or comparable selection positions according • to MIL
- With table for calculating the settings •
- Pliers in a plastic case with foam insert •
- Without locator •
- For crimping turned contacts Four-mandrel crimping for top-quality crimp connections
- • Mandrel gauge to check the basic setting
- Repetitive, high crimping quality due to ratchet mechanism • (unlockable)
- Optimum transmission of force due to highly effective lever action for • fatigue-reduced operation
- High operation comfort thanks to handy shape •

MM 🗶

General

97 52 65 DG A
4003773071990
chrome-plated
chrome-plated
with multi-component grips
633 g
250 x 86 x 19 mm
contains SVHC
not applicable

Technical details

Application	turned contacts (Harting; Ilme; Phoenix; Amphenol; Walther; HTS; Contact; Weidmüller)	
Capacity in square millimetres	0.14 — 6 mm²	
AWG	26 — 10	
Number of crimp profiles	1	
Max. contact diameter	7.5 mm	
Accessories		
97 59 65 2	Universal Locator for 97 52 65 / 97 52 65 A / 97 52 65 DG / 97 52 65	

DG A,

technical change and errors excepted